



SORAA 7.5W LED MR16 4000K VIVID3 25° DIM

Item #777061

Ordering Code SM16-07-25D-940-03

UPC 849565009376

- Works with trailing edge and leading edge phase cut dimmers
- Enclosed fixture compatibility allows operation in damp or outdoor locations
- White point accuracy within 3 SDCM
- CUL rated for 12VAC NEC Class 1 and Class 2 systems
- SORAA SNAP SYSTEM compatible with spot models
- VIVID lamps offer excellent color rendering: CRI = 95 & R9 = 95
- 7.5W LED = 50W HALOGEN
- \*Energy Star Qualified



## TECHNICAL SPECIFICATIONS

Item #	Watts	Bulb Type	Base	Volts	Finish/Description	Beam Angle (°)	Color Temperature (CCT)
777061	7.5	MR16	GU5.3	12	N/A	25	4000K
Color	CRI	Lumens	CBCP	Average Hours	M.O.L. (inches)	M.O.D. (inches)	Incandescent Equivalent
Cool White Light	95	455	2510	35000	1.875	2.000	50W
Energy Star	DLC	Title 24 Compliant	Safety Rated	Safety Rating	Type Enclosed	Rated	Dimmable
N	N	N	UL	DAMP	Y	Y	Warranty
							3

Order Multiple  
QTY  
10

## APPLICATION SUGGESTIONS



Landscape



Recessed



Track

