

## **UL SPECIFICATION**

\* FIXTURE SHALL BE LISTED FOR LOCATION ONLY AND LABELED AS SUCH. \* FIXTURE MUST BE MANUFACTURED IN ACCORDANCE WITH UL STANDARD 1598.

## PARTS SPECIFICATIONS ITEM OTY DESCRIPTION

- A (1) SOCKET- UL LISTED/CSA CERTIFIED BASE=MEDIUM SOCKET=PORCELIN SEE LEAD WIRE FOR SOCKET WIRE SPEC.
- В (1) LEAD WIRE- 10FT FROM SHADE UL LISTED/CSA CERTIFIED, AWG #18 105°C BLACK AND WHITE WIRE. STRIP 1/2 [12.7], SPLIT 3 [76.2]. FROM TOP OF SCROLL. (SEE CHART FOR COLOR).
- GROUND WIRE- 7" [180] FROM CANOPY (1) 1/4 LAY COPPER GROUND WIRE. FROM TOP OF SCROLL. (SEE CHART FOR TINT).

PART NO.	DESCRIPTION	REQ.
	PART NO.	PART NO. DESCRIPTION

## INNOVATIONS CREATIVITY MEETS EVOLUTIONARY DESIGNO

"mm" DIMENSION INDICATED IN [] DRAWN IN DIMENSION IN [] IS FOR REF. ONLY THIRD ANGLE TOLERANCES (EXCEPT AS NOTED) PROJECTION DECIMAL ANGULAR FRACTIONAL SCALE NONE ±.031 ± 1/2° ± 1/32 1:7 DATE SSL Χ .XXX ±.005 26/11/2019

TITLE **1LT PENDANT** 

REV. PART NO. REVB

ITEM NO. 650-1P-BC-16