
# **CERVANTES** 56" Ceiling Fan

FR-W1806-56L

# MODERN FORMS SMART FANS





#### **PRODUCT DESCRIPTION**

Modern luxury is all about making life simpler- that's exactly what Cervantes does for you. With our Modern Forms app, you can map out schedules, optimize energy use and integrate with smart home devices you already own, like Amazon Alexa and Google Assistant. And Cervantes's clean, offset blades slice through the air with barely a whisper- that's because the powerful DC motor keeps things running smooth and super quiet. Available in versatile oil-rubbed bronze and graphite finishes.

#### **SPECIFICATIONS**

Construction: Aluminum

Blade: 14° Pitch, 56" sweep, ABS

Downrod: 1" O.D. x 4.5"H included

Mounting Slope: Up to 30°

Lead Wire: 80"

Hanging Weight: 20 lbs
Total Power: 48.5W

Standards: ETL/cETL Wet Location listed

#### **FEATURES**

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional LED light kit included
- Includes RF wall control
- Additional RF wall control for 3, 4-way control sold separately
- Compatible with Modern Forms app

### LIGHT KIT PERFORMANCE

Light Source: LED Light Wattage: 19.5W Dimming: Integrated

Color Temperature: 3000K (2700K / 3500K options available)

Rated Life: 50,000 Hours

Standards: Title 24 JA8-2016 Compliant

#### **ESTIMATED AIR PERFORMANCE**

Airflow: 6577 cubic ft per minute on high

Power: 29 watts on high

**Airflow Efficiency:** 228 cubic ft per minute per watt **Revolutions Per Minute:** 153 RPMs on high

#### WIRELESS PERFORMANCE

RF Pairing Distance: Up to 30 ft from fan

Wi-Fi Range: Up to 150 ft\*

# ORDER NUMBER

Model	LED Lumens	Delivered Lumens		Housing		Blade	
FR-W1806-56L	1600	429	GH OB	Graphite Oil Rubbed Bronze	DW WG	Dark Walnut Weathered Gray	

Example: FR-W1806-56L-GH/DW

For 2700K add "27"; 3500K add "35" before the finish: FR-W1806-56L27OBDW

\*Results may vary based on application and surroundings.





modernforms.com Phone (866) 810.6615 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

OPTIONAL ACCESSORIES								
RF Wall Control F-WC		wt	White	Control fan speed, light brightness and switch between Summer and Winter Modes from up to 30 ft away. One RF Wall control comes standard with each Modern Forms Smart fan.				
RF Remote Control	F-RC	wt	White	Sold separately. Control fan speed and light brightness, and switch between Summer and Winter Modes from up to 50 ft away. Includes easy-to-install cradle and batteries.				
Wi-Fi Touch Panel Wall Control	F-TS	BK WT	Black White	Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.				
Downrod	XF-12 12in XF-18 18in XF-24 24in XF-36 36in XF-48 48in XF-60 60in XF-72 72in	AS BA BZ CFI	Automotive Silver Brushed Aluminum Bronze Carbon Fiber** Dark Walnut Gloss Black Graphite Gloss White Koa†	All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.				
Downrod Couplers	XF-I	GB GH GW KO		Connects two downrods together.				
Sloped Ceiling Kit  XF-SCK		MB MW OB SS TT	Matte Black Matte White Oil Rubbed Bronze Stainless Steel Titanium Silver	Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.				

Examples: RF Wall Control - F-WC-WT, RF Remote Control - F-RC-WT, Wi-Fi Touch Panel - F-TS-WT, Downrod - XF-12-BZ, Downrod Coupler - XF-I-BZ, Sloped Ceiling Kit - XF-SCK-DW

# SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15′	14′	13'	12'	11′	10′	9′
Downrod	72"	60"	48"	36"	24"	18"	12"

# SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire

\*\*Carbon Fiber downrods available in 12", 18", 24" and 36"

\*Koa downrods available in 12", 18", 24" and 36"

modernforms.com Phone (866) 810.6615 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760