
MODERN FORMS SMART FANS





PRODUCT DESCRIPTION

As bold and beautiful as a classic Holland windmill, this contemporary twelve-blade design is perfect for mid-sized and larger spaces with its 60 inch or 80 inch blade sweeps. Control everything from the palm of your hand with our Wi-Fi-connected Modern Forms app- no one else in the industry can match this combination of style and intuitive technology. Available in three sleek finishes, Windflower makes life easier and more beautiful every day.

SPECIFICATIONS

Construction: Aluminum

Blade: 12° Pitch, 60" sweep, ABS

Downrod: 1" O.D. x 6"H included

Mounting Slope: Up to 30°

Lead Wire: 80"

Hanging Weight: 34.5 lbs **Total Power:** 72.5W

Standards: ETL/cETL Wet Location listed

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional LED light kit included
- Includes RF wall control
- Additional RF wall control for 3, 4-way control sold separately
- Compatible with Modern Forms app

LIGHT KIT PERFORMANCE

Light Source: LED Light Wattage: 23.5W Dimming: Integrated

Color Temperature: 3000K (2700K / 3500K options available)

Rated Life: 50,000 Hours

Standards: Title 24 JA8-2016 Compliant

ESTIMATED AIR PERFORMANCE

Airflow: 8840 cubic ft per minute on high

Power: 49 watts on high

Airflow Efficiency: 180 cubic ft per minute per watt **Revolutions Per Minute:** 128 RPMs on high

WIRELESS PERFORMANCE

RF Pairing Distance: Up to 30 ft from fan

Wi-Fi Range: Up to 150 ft*

ORDER NUMBER

Model	LED Lumens	Delivered Lumens		Housing		Blade	
FR-W1815-60L			ОВ	Oil Rubbed Bronze	DW	Dark Walnut	
	2041	1080	GH	Graphite	WG	Weathered Gray	
			МВ	Mate Black	DK	Distressed Koa	

Example: FR-W1815-60L-GH/WG

For 2700K add "27"; 3500K add "35" before the finish: FR-W1815-60L27MBDK

*Results may vary based on application and surroundings.





modernforms.com Phone (866) 810.6615 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WINDFLOWER 60" Ceiling Fan

FR-W1815-60L



OPTIONAL ACCESSORIES									
RF Wall Control F-WC			WT White		Control fan speed, light brightness and switch between Summer and Winter Modes from up to 30 ft away. One RF Wall control comes standard with each Modern Forms Smart fan.				
RF Remote Control	F-RC		WT	White	Sold separately. Control fan speed and light brightness, and switch between Summer and Winter Modes from up to 50 ft away. Includes easy-to-install cradle and batteries.				
Wi-Fi Touch Panel Wall Control	F-TS		BK WT	Black White	Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.				
Downrod Couplers	XF-18 1: XF-24 2: XF-36 3: XF-48 4: XF-60 6:	6in 8in Oin 2in	AS BA BZ CFI DW GB GH GW KO	Automotive Silver Brushed Aluminum Bronze Carbon Fiber** Dark Walnut Gloss Black Graphite Gloss White Koa†	All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field. Connects two downrods together.				
Sloped Ceiling Kit XF-SCK		MB MW OB SS TT	Matte Black Matte White Oil Rubbed Bronze Stainless Steel Titanium Silver	Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.					

Examples: RF Wall Control - F-WC-WT, RF Remote Control - F-RC-WT, Wi-Fi Touch Panel - F-TS-WT, Downrod - XF-12-BZ, Downrod Coupler - XF-I-BZ, Sloped Ceiling Kit - XF-SCK-DW

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15′	14′	13'	12'	11'	10′	9′
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire

**Carbon Fiber downrods available in 12", 18", 24" and 36"

modernforms.comHeadquarters/Eastern Distribution CenterPhone (866) 810.661544 Harbor Park DriveFax(800) 526.2585Port Washington, NY 11050

Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

^{*}Koa downrods available in 12", 18", 24" and 36"