



### TECHNICAL DETAILS

ADA Compliance: Yes	Water Pressure Recommended: 60 PSI
Deck Thickness Maximum: 2"	
Deck Thickness Minimum: 1/8"	
Drain Assembly Material: Brass	
Drain Style: Lift pop-up	
Fitting Hole Diameter: 1 1/8"	
Number of Holes: Three Hole	
Number of Handles: Two	
Handle Spread Maximum: 12"	
Handle Spread Minimum: 8"	
Handle Turn Angle: Quarter Turn	
Spout Reach: 6 1/2"	
Spout Height: 9 7/8"	
Inlet Connection Type: Male 1/2" NPSM	
Installation Type: Deck Mounted	
Primary Material: Brass	
Valve Material: Ceramic	
Flow Restriction: 1.2 gpm	
Water Pressure Maximum: 85 PSI	
Water Pressure Minimum: 20 PSI	

### PRODUCT FEATURES

- Style: Contemporary
- Collection: Basic II
- Temperature Controlled By Handles
- Lever Handles

### CODES & STANDARDS



ASME A112.181/ CSA B125.1, ASME 112.18.2/ CSA B125.2, ANSI NSF, CEC, Watersense 61 Sect. 9, State of MA.

### WARRANTY

Mechanical Warranty: 10 Years from date of purchase.  
Finish Warranty: See catalog for further information.

